

**Product Data Sheet**

**Application:** HVAC

# Isover Climcover Slab Alu2 Standard



## HVAC - Thermal Insulation for Metal Ductwork

Isover Climcover Slab Alu2 Standard is a robust glass mineral wool slab which can be considered for the thermal insulation of rectangular metal ductwork. The slabs are lightweight and feature a factory applied aluminium foil facing providing an inherent vapour barrier and a professional finish.

With increased mechanical performance when compared to Isover Climcover Slab Alu2, it offers a high quality finish and can be considered for applications inside a building or outside (with suitable covering).

## Features and Benefits



**THERMAL  
INSULATION**

Offers energy savings through helping to control temperatures and reduce heat loss or gain within ductwork.



**RENEWABLE  
ELECTRICITY**

All electric equipment in the plant powered by 100% renewable electricity.



**A2 FIRE  
CLASSIFICATION**

Achieves a Euroclass A2-s1,d0 Reaction to Fire classification, according to EN 13501-1.



**CONTAINS  
RECYCLED  
GLASS**

Isover Climcover Slab Alu2 Standard contains recycled glass. A combination of 52% externally sourced recycled glass and 30% internally sourced glass cullet



**EASE  
OF INSTALL**

Lightweight and provides a combination of flexibility and mechanical strength, allowing fast and efficient cutting and fitting. It offers consistent thickness recovery and a uniform shape with no soft edges, to obtain a neat and professional finish.

# Key Considerations

When using Isover Climcover Slab Alu2 Standard you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire.

Please refer to [isover.co.uk](http://isover.co.uk) for all current documentation relating to this product.

## Product Specification

Product code	Thickness (mm)	Length (mm)	Width (mm)	Slabs per pack	Pack area (m <sup>2</sup> )	Packs per pallet	Pallet area (m <sup>2</sup> )
5200625471	40	1200	600	11	7.92	16	126.72
5200625473	50	1200	600	9	6.48	16	103.68

## Thermal Conductivity

Mean temp °C	10	40	50	100	120
Declared thermal conductivity (W/m.K)	0.032	0.037	0.038	0.047	0.051

## Characteristics

<b>External Application</b>	Can be considered for external applications when used with an appropriate weatherproof jacketing system.
<b>Service Temperature</b>	Can be considered for continuous service temperatures from 5°C to 150°C. The temperature on the aluminium facing should not exceed 80°C. For applications over 150°C, please contact our Technical Support Centre. When using the product for the insulation of ductwork with a surface temperature below dew point, care must be taken to ensure a 100% vapour barrier is maintained.
<b>Environmental</b>	All Isover products are manufactured under Environmental Management System - ISO 14001.
<b>Indoor Air Quality</b>	Achieves a Eurofins Gold product status for indoor air quality.

<b>Certification</b>	UKCA Marked to EN 14303. CE marked to EN 14303. Designation code: MW-EN 14303-T3.
<b>Handling, Storage, Health and Safety</b>	Information regarding storage, installation and handling of Isover products and health and safety information can be found at <a href="http://isover.co.uk/suis">isover.co.uk/suis</a> .
<b>Quality</b>	All Isover products are manufactured under Quality Management Standard - ISO 9001.
<b>EUCEB</b>	EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008.



**Isover**

Saint-Gobain Isover UK Limited,  
Saint-Gobain House, East Leake, Loughborough,  
Leicestershire, LE12 6JU.

**Customer Service -  
Order Placement and Enquiries**

Tel: 0800 0322 555  
Email: [isover.customerservice@saint-gobain.com](mailto:isover.customerservice@saint-gobain.com)

**Technical Support Team**

Email: [isover.technical@saint-gobain.com](mailto:isover.technical@saint-gobain.com)

**[isover.co.uk](http://isover.co.uk)**

Published date: 03 March 2026

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at [isover.co.uk](http://isover.co.uk)

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.