


Product Data Sheet

Application: HVAC

Isover U Protect Wired Mat 4.0 Alu1



Isover Ultimate™ mineral wool wired mats for fire protection of circular ductwork.

The Isover U Protect system is certified to deliver up to two hours of passive fire protection for HVAC mechanical ventilation and smoke extract ducts. It has been tested in accordance with EN 1366-1 and EN 1366-8 and assessed against the criteria in EAD 350142-00-1106 under ETA 18/0691.

For circular ductwork, the Isover U Protect Wired Mat 4.0 Alu1 is manufactured from Ultimate mineral wool and supplied in 600 mm wide rolls. Ultimate mineral wool provides conventional thermal insulation and also achieves a Euroclass A1 fire classification. Fire resistance is dependent on the application, insulation thickness, and installation method.

Features and Benefits



Tested to European standards and CE marked in accordance with EAD 350142-00-1106 providing up to 2 hours passive fire protection to HVAC ventilation and smoke extract ductwork.



Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



Offers energy savings through helping to control temperatures and reduce heat loss or gain within ductwork.



The Ultimate™ wired mats offer a lightweight solution compared to traditional stone wool options, ensuring ease of handling and installation, as well as reducing the stress on supporting structures. Their flexibility and mechanical strength allows fast and efficient cutting and fitting. The adhesive used in the system is only required at penetration details rather than at every insulation joint.

Key Considerations

When using Isover U Protect Wired Mat 4.0 Alu1 you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire.

Please refer to isover.co.uk for all current documentation relating to this product.

Product Specification

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m ²)	Packs per pallet	Weight per m ² (kg)	Pallet area (m ²)
5200864101	30	10.00	2 x 0.60	12.00	18	2.30	216.00
5200687131	50	6.00	2 x 0.60	7.20	18	3.60	129.60
5200687132	60	5.00	2 x 0.60	6.00	18	4.30	108.00
5200680831	75	4.00	2 x 0.60	4.80	18	5.30	86.40
5200687133	80	3.70	2 x 0.60	4.44	18	5.60	79.92
5200864775	90	3.30	2 x 0.60	3.96	18	6.30	71.28
5200687134	100	3.00	2 x 0.60	3.60	18	6.90	64.80
5200680832	120	2.50	2 x 0.60	3.00	18	8.30	54.00

Thermal Conductivity

Mean temp °C	10	50	100	150	200	300	400
Declared thermal conductivity (W/m.K)	0.031	0.035	0.040	0.047	0.054	0.072	0.096

Characteristics

Application	Use Isover U Protect Wired Mat 4.0 Alu1 on circular ductwork to provide up to two hours passive fire protection in HVAC ventilation and smoke extraction ducts. Must be used in conjunction with U Protect Accessories as tested. For further details, please visit isover.co.uk/hvac-insulation/duct-insulation-fire-protection .	Environmental	All Isover products are manufactured under Environmental Management System – ISO 14001.
External Application	Isover U Protect Wired Mat 4.0 Alu1 is not suitable for external use.	Certification	UKCA Marked to EN 14303. CE marked to EN 14303. Designation code: MW-EN-14303-T2-ST(+)-400
Maximum Service Temperature	400°C	Handling, Storage, Health and Safety	Information regarding storage, installation and handling of Isover products and health and safety information can be found at isover.co.uk/suis .
Facing	Isover U Protect Wired Mat 4.0 Alu1 is faced on one side with a black aluminium foil and reinforced with a galvanised steel grid.	Quality	All Isover products are manufactured under Quality Management Standard – ISO 9001.
		EUCEB	EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008.



Isover

Saint-Gobain Isover UK Limited,
Saint-Gobain House, East Leake, Loughborough,
Leicestershire, LE12 6JU.

**Customer Service -
Order Placement and Enquiries**

Tel: 0800 0322 555
Email: isover.customerservice@saint-gobain.com

Technical Support Team

Email: isover.technical@saint-gobain.com

isover.co.uk

Published date: 03 March 2026

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at isover.co.uk

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.